

# DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type:

Code: **5980**

Size: **1/4" - 1/2" - 3/4" - 1" - 1"1/4 - 1"1/2 - 2"**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Production date printed on valve body, on packaging or on delivery note**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**It applies to metallic valves for domestic and commercial not directly buried installations inside or outside of buildings, using gases of the first, second and third family (specified in EN 437)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**RUBINETTERIE BRESCIANE BONOMI S.p.A. - Via Massimo Bonomi, 1 – 25064 Gussago (Brescia) - Italy**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**Bsi, Kitemark Court, Knowlhill, Milton Keynes MK58PP**  
performed: **type tests and annual production monitoring**  
and issued: **0086 - CPD- 592485**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not applicable**

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Gas families	1 <sup>st</sup> , 2 <sup>nd</sup> , 3 <sup>rd</sup> family gases	EN 331:1998/A1:2010
Nominal size	point 1	
Internal pressure	5 bar (0.5 MPa)	
Leak-tightness	20 cm <sup>3</sup> /h	
Pressure class	MOP 5 (external to buildings)	
Fire resistance pressure class	MOP 1 (internal to buildings)	
Temperature range	da -20°C a 60°C	
Resistance to high temperature	650°C per 30 min	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

The company works according to an integrated QUALITY, ENVIRONMENTAL and SAFETY management system which complies with the standards ISO\_9001, ISO\_14001 and OHSAS\_18001, recognised by SQS.

Gussago,

16/06/2015

Carlo Bonomi \*

(place and date)

Carlo Bonomi (General Manager)

\* electronic signature: the original signature is available in our company