




Serie **EXPO-SFER**

Articolo **1821**

Full bore ball valve, M/F threaded, with aluminium T-handle.



POS.	PART NAME	MATERIALE-MATERIALS MATERIAUX-WERKSTOFF- MATERIAL	N°P
1	BODY	OTTONE CW617N UNI EN 12165	1
2	END CONNECTION	OTTONE CW617N UNI EN 12165	1
3	BALL	OTTONE CW617N UNI EN 12165	1
4	STEM	OTTONE CW614N UNI EN 12164	1
5	PACKING GLAND	OTTONE CW614N UNI EN 12164	1
6	HANDLE	ALLUMINIO EN-AC 46100 EN 1706	1
7	BALL SEAT	P.T.F.E	2
8	STEM SEAL/TRUST WASHER	P.T.F.E	2
9	O-RING	NBR	1
10	DADO	ACCIAIO CL 04	2

MISURA SIZE	DN	BOX	MASTER BOX	CODICE CODE	ØP	I	I1	L	ØH	Ch	M	h	Kv	PN	Kg
1/4"*	8	25	50	1721020000	10	11	11	59	23	20	50	42	5,4	64	0,13
3/8"*	10	25	50	1721030000	10	11,4	11,4	59,5	23	20	50	42	6	64	0,13
1/2"	15	50	100	1821040000	15	13,5	13	64,5	33	25	50	46	16,3	30	0,20
3/4"	20	30	60	1821050000	20	12,5	16,5	73	39	31	64	56	29,5	30	0,31
1"	25	20	40	1821060000	25	15	19	85	49	38	64	60	43	30	0,50

Limiti di temperatura: -20°C +160°C - Temperature range: -20°C +160°C.

* Art.1721



**RUBINETTERIE
BRESCIANE**

